

**Safety Data Sheet**  
**THOMAS REMOVE-ALL TAR & ASPHALT REMOVER**

**SECTION I - IDENTIFICATION**

**PRODUCT IDENTIFIER:** THOMAS REMOVE-ALL TAR & ASPHALT REMOVER  
**PRODUCT CODE:** 4713182101  
**RECOMMENDED USE:** Tar & Asphalt Remover  
**RESTRICTIONS ON USE:** None Known  
**COMPANY NAME:** Thomas Supply & Distribution  
**COMPANY ADDRESS:** 3111 CRD 127, Midland, TX 79706  
**COMPANY PHONE:** 432-634-9736  
**EMERGENCY PHONE:** 432-488-6885



**SECTION II – HAZARDS IDENTIFICATION**

**CLASSIFICATION:** Flammable Aerosol: Category 1

Liquefied Gas

Eye Damage: Category 1

Skin Irritant: Category 2

Skin Sensitization: Category 1B

Aspiration Hazard: Category 1

**HAZARD STATEMENT(S): DANGER:** Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin irritation and serious eye damage. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Wear eye/face protection and protective gloves. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash hands thoroughly after handling. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing dust/fume/gas/mist/vapors/spray. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents in accordance with local, state, and federal law.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

**SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Distillates (petroleum), hydrotreated light	64742-47-8	50- 60%
d-Limonene	5989-27-5	20-30%
Propane	74-98-6	10-15%
Nonoxynol	127087-87-0	5-10%
Isobutane	75-28-5	0.1-1%

**SECTION IV - FIRST AID MEASURES**

**EYES:** Immediately flush with water for 15 minutes while holding eyelids open. Seek immediate medical attention.

**INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center.

**INHALATION:** Move to fresh air. If not breathing, administer artificial respiration.

**SKIN:** Wash thoroughly with soap and water. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Oral: Aspiration risk

**CHRONIC HEALTH HAZARDS:** None known

**Safety Data Sheet**  
**THOMAS REMOVE-ALL TAR & ASPHALT REMOVER**

**NOTE TO PHYSICIAN:** There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

**SECTION V – FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, foam, and water spray or fog.

**UNSUITABLE EXTINGUISHING MEDIA:** N/A

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear SCBA in fire situations.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Keep away from heat, sparks, open flames and other sources of ignition. Contains flammable propellant.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon

**SECTION VI – ACCIDENTAL RELEASE MEASURES**

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Eliminate all sources of ignition. Absorb spill with non-combustible material such as vermiculite, sand or earth.

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not reuse, puncture, or incinerate container. Wrap container and place in trash collection.

**RCRA STATUS:** Product should be fully characterized prior to disposal (40 CFR 261).

**SECTION VII – HANDLING AND STORAGE**

**HANDLING AND STORAGE:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Strong alkalis, oxidizers, bases, reactive metals, and natural rubber

**SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION**

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated light	400 ppm	400 ppm
d-Limonene	Not Established	Not Established
Propane	1000 ppm	1000 ppm
Nonoxynol	Not Established	Not Established
Isobutane	1000 ppm	1000 ppm

**ENGINEERING CONTROLS / VENTILATION:** General ventilation adequate.

**RESPIRATORY PROTECTION:** Avoid breathing vapor.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Liquid, Clear to Slight Tint

**ODOR:** Citrus

**ODOR THRESHOLD:** N/D

**pH:** N/D

**MELTING POINT/FREEZING POINT:** N/D

**INITIAL BOILING POINT AND BOILING RANGE:** N/D

**FLASH POINT:** N/D

**EVAPORATION RATE:** N/D

**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol

**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**EXPLOSIVE LIMIT LOWER (%):** N/D

**EXPLOISVE LIMIT UPPER (%):** N/D

**Safety Data Sheet**  
**THOMAS REMOVE-ALL TAR & ASPHALT REMOVER**

**VAPOR PRESSURE (mm Hg):** N/D  
**VAPOR DENSITY (AIR=1):** N/D  
**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.85 - 0.95  
**SOLUBILITY(IES):** Miscible  
**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D  
**AUTOIGNITION TEMPERATURE:** N/D  
**DECOMPOSITION TEMPERATURE:** N/D  
**VISCOSITY:** N/D

**SECTION X – STABILITY AND REACTIVITY**

**REACTIVITY:** If exposed to strong oxidizers, presents explosion hazard.  
**CHEMICAL STABILITY:** Stable  
**POSSIBLE HAZARDOUS REACTIONS:** None Known  
**CONDITIONS TO AVOID:** Temperatures greater than 122°F and sources of ignition.  
**INCOMPATIBLE MATERIALS:** Strong alkalis, oxidizers, bases, reactive metals, and natural rubber  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon

**SECTION XI – TOXICOLOGICAL INFORMATION**

**TOXICOLOGICAL INFORMATION:** Distillates (petroleum), hydrotreated light (64742-47-8) LD<sub>50</sub> (Oral, Rat) >5000 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) >2000 mg/kg  
**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin  
**EYES:** Causes irritation, redness, tearing.  
**INGESTION:** Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomiting, abdominal cramps. Aspiration hazard.  
**INHALATION:** May cause dizziness and/or headaches.  
**SKIN:** Causes localized defatting, irritation, dermatitis.  
**MEDICAL CONDITION AGGRAVATED:** None known  
**ACUTE HEALTH HAZARDS:** Oral: Aspiration risk  
**CHRONIC HEALTH HAZARDS:** None known  
**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

**SECTION XII – ECOLOGICAL INFORMATION**

**ECOTOXICITY:** Distillates (petroleum), hydrotreated light (64742-47-8) Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility. May adsorb to sediments and possibly cause toxic effects to organisms.  
**PERSISTENCE AND DEGRADABILITY:** This product is biodegradable.  
**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.  
**MOBILITY IN SOIL:** This product is mobile in soil.  
**OTHER ADVERSE EFFECTS:** None Known

**SECTION XIII – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not reuse, puncture, or incinerate container. Wrap container and place in trash collection.  
**RCRA STATUS:** Product should be fully characterized prior to disposal (40 CFR 261).

**SECTION XIV - TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A

**AIR SHIPMENT**

**PROPER SHIPPING NAME:** Aerosols, flammable  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950

**Safety Data Sheet**  
**THOMAS REMOVE-ALL TAR & ASPHALT REMOVER**

**PACKING GROUP:** N/A

**SHIPPING BY WATER:**

**VESSEL (IMO/IMDG)**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKING GROUP:** N/A

**ENVIRONMENTAL HAZARDS WATER:** N/A

**SECTION XV - REGULATORY INFORMATION**

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** None

**SARA 311/312 HAZARD CATEGORIES:** Fire Hazard

**SARA 313 REPORTABLE INGREDIENTS:** None

**STATE REGULATIONS:** California Proposition 65: None

**INTERNATIONAL REGULATIONS:** All components are listed or exempted.

**VOLATILE ORGANIC COMPOUNDS (VOC):** 36.5%

**NFPA HEALTH:** 1

**NFPA FLAMMABILITY:** 3

**NFPA REACTIVITY:** 1

**NFPA OTHER:** None

**HMIS HEALTH:** 1

**HMIS FLAMMABILITY:** 3

**HMIS REACTIVITY:** 1

**HMIS PROTECTION:** B

**SECTION XVI - OTHER INFORMATION**

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.